

Quick connect pressure spray nozzles

DESIGN FEATURES

1. Large color coded rings permit rapid identification of the spray angle.
2. Hardened stainless steel orifices provide superior wear resistance.
3. Solid stainless steel housing resists cracking and wear.
4. High impact design with uniform distribution.
5. Quick connect for easy installation.
6. Fast alignment and easy spray pattern direction.
7. Recommended for use with 4-7HP pressure washers.
8. Use as directed in the pressure washer's owner manual.

Spray Characteristics:

1. Spay pattern: flat fan
2. Spray angles: 0°, 15°, 25°, 40°



0°-1/4"
Quick-connect



15°-1/4"
Quick-connect



25°-1/4"
Quick-connect



45°-1/4"
Quick-connect

PERFORMANCE DATA

Capacity size	Orifice dia.	Capacity liters per minute																				
		20bar 290psi	30bar 430psi	40bar 580psi	50bar 700psi	60bar 850psi	70bar 1000psi	80bar 1200psi	90bar 1300psi	100bar 1450psi	110bar 1600psi	130bar 1900psi	140bar 2000psi	150bar 2180psi	160bar 2300psi	180bar 2600psi	200bar 2900psi	220bar 3200psi	250bar 3600psi	280bar 4100psi	310bar 4500psi	240bar 5000psi
020	0.87	2.0	2.5	2.8	3.2	3.5	3.7	4	4.2	4.5	4.7	5.1	5.3	5.5	5.7	6.0	6.4	6.7	7.6	8.5	9.4	10.3
025	0.97			3.6	4.1	4.4	4.8	5.1		5.6			6.6	7.0			8.1					
030	1.05	3.1	3.7	4.3	4.8	5.3	5.7	6.1	6.3	6.8	7.2	7.7	8	8.3	8.7	9.2	9.6	10	11.4	12.8	14.2	15.6
035	1.12	3.6	4.4	5.1	5.6	6.0	6.5	7.0	7.4	7.8	8.2	8.9	9.2	9.6	9.9	10.5	11	11.6	12.3	13.1	13.7	14.4
040	1.21	4.2	5.2	5.9	6.6	7.0	7.6	8.1	8.6	9.1	9.5	10.4	10.8	11.1	11.5	12.2	12.9	13.5	14.4	15.2	16	16.8
045	1.30	4.5	5.5	6.4	7.1	7.8	8.6	9.2	9.8	10.3	10.8	11.7	12.2	12.6	13	13.8	14.6	15.3	16.3	17.2	18.1	19
050	1.35	5.0	6.2	7.1	8.0	8.7	9.4	10	10.7	11.4	12	12.9	13.4	14	14.4	15.3	16.1	16.9	17.9	19.1	20.1	21
055	1.40	5.6	6.8	7.8	8.7	9.6	10.5	11.2	11.9	12.5	13.1	14.3	14.8	15.3	15.8	16.8	17.7	18.5	19.8	20.9	22	23
060	1.50	6.0	7.4	8.6	9.6	10.6	11.5	12.3	13	13.7	14.4	15.6	16.2	16.8	17.3	18.4	19.4	20.3	21.7	22.9	24.1	25.3
065	1.55	6.6	8.0	9.3	10.4	11.3	12.3	13.2	14	14.8	15.5	16.9	17.4	18.1	18.7	19.9	20.9	22	23.4	24.8	26.1	27.3
070	1.60	7.1	8.6	10	11.2	12.2	13.2	14.1	15	15.8	16.6	18	18.7	19.3	20.1	21.3	22.3	23.7	25	26.3	27.6	28.9
075	1.65	7.6	9.3	10.7	12	13.1	14.2	15.2	16.1	16.9	17.7	19.2	20	20.7	21.4	22.6	23.8	25.3	26.7	28.1	29.5	30.9
080	1.70	8.0	9.8	11.3	12.7	14	11.1	16.1	17.1	18	18.9	20.5	21.3	22	22.8	23.8	25.4	27	28.5	30	31.5	33
085	1.75	8.5	10.4	12.1	13.5	14.8	16	17.1	18.1	19.1	20	21.7	22.5	23.4	24	25.5	27	28.2	30	31.8	33.6	35.4
090	1.80	9.1	11.1	12.8	14.3	15.7	17	18	19.2	20.2	21.2	23	23.9	24.7	25.5	26.7	28.5	30.3	31.9	33.5	35.1	36.7
095	1.85	9.7	11.9	13.4	15.4	16.8	18.1	19.4	20	21.7	22.7	24.7	25.9	26	26.7	28.5	30	31.5	33.2	34.9	36.6	38.3
100	1.90	10	12.3	14.2	16	17.4	18.9	20.1	21.4	22.5	23.6	25.6	26.6	27.7	28.5	29.8	31.8	33.7	35.6	37.5	39.4	41.3
110	1.98	11.1	13.6	15.7	17.6	19.3	20.8	22.2	23.6	24.9	25.5	27.7	28.8	29.9	30.8	32.6	34.4	36	38.4	40.8	43.2	45.6

ORDERING INFORMATION

